

## Platform Indicator Display

**mod. TL02-04**

**mod. TL02-05 (with Clock)**

Devices made in LED technology, are part of a line of devices for displaying information to travelers in public transportation applications.

The structure of the LED panel makes this type of devices dedicated to the display of information on events related to a particular structure (destination, time, delay departure of trains from a platform or bus from a shelter).

The high performance of optical brightness, contrast and angle of vision allow to use them in outdoor environments with strong light, even in the presence of sunlight.

The devices, thanks to the characteristics of the operating system and application software on board, are able to view any information screen so to allow the use of these in many different areas (web applications, etc.).



mod. TL02-04



mod. TL02-05

Configuration	TL02-04 (Double-sided)	TL02-05 (Double-sided)
<b>LED</b>		
Technology		AllnGaP
Color		Yellow
Diameter (mm)		4
Brightness (cd/mq)		6000
Contrast		> 5
<b>CONSUMPTION</b>		
Pmax (70% max brightness LED lit)	500 W	550 W
Pmed (typical use)	350 W	400 W
<b>OVERALL</b>		
Dimensions (mm)	1350 x 747 x 350	1690 x 747 x 350
<b>WEIGHT</b>		
Device (kg)	97	115
Bracket (kg)	37	40
<b>PROTECTION</b>		
Grade		IP55